

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 September 2005 (22.09.2005)

PCT

(10) International Publication Number
WO 2005/088014 A1

(51) International Patent Classification⁷: **E01C 19/17**,
B05B 1/16, 1/20, 1/32

(21) International Application Number:
PCT/IB2005/050756

(22) International Filing Date: 2 March 2005 (02.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
531536 2 March 2004 (02.03.2004) NZ

(71) Applicant and

(72) Inventor: WILLIAMS, Timothy [NZ/NZ]; 3 Cliff Street,
Wanaka (NZ).

(74) Agent: FOSTER, John; Shelston IP, 60 Margaret Street,
Sydney, NSW 2000 (AU).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: IMPROVEMENTS IN OR RELATING TO SPRAYING APPARATUS



(57) **Abstract:** A spray bar typically utilised for the application of fluids such as hot bitumen onto an adjacent surface has an inner tube (2) which is rotatable relative to an outer tube (17) byway of an actuator (24). The outer tube (17) has various spray nozzles (21) which are designed to deliver fluid fed to the spray bar through a fluid supply passage (3), onto the adjacent surface. The rate of flow to each nozzle is controlled by a series of corresponding apertures in the inner tube (2) and the outer tube (17) which are moved into or out of alignment by rotation of the inner tube relative to the outer tube via the actuator (24). By providing different patterns of apertures corresponding to different nozzles (21) it is possible to achieve altering spray patterns by rotation of the inner tube relative to the outer tube into predetermined orientations. The spray bar according to the invention also has the advantage over the prior art of simplified actuation controls and more robust and reliable construction.



WO 2005/088014 A1